

Safety & Environmental Enforcement, Interior

§ 250.300

(e) Information concerning the drilling and completion systems;

(f) Design and fabrication information for each riser system (e.g., drilling, workover, production, and injection);

(g) Pipeline information;

(h) Information about the design, fabrication, and operation of an offtake system for transferring produced hydrocarbons to a transport vessel;

(i) Information about subsea wells and associated systems that constitute all or part of a single project development covered by the DWOP;

(j) Flow schematics and Safety Analysis Function Evaluation (SAFE) charts (API RP 14C, subsection 4.3c, incorporated by reference in §250.198) of the production system from the Surface Controlled Subsurface Safety Valve (SCSSV) downstream to the first item of separation equipment;

(k) A description of the surface/subsea safety system and emergency support systems to include a table that depicts what valves will close, at what times, and for what events or reasons;

(l) A general description of the operating procedures, including a table summarizing the curtailment of production and offloading based on operational considerations;

(m) A description of the facility installation and commissioning procedure;

(n) A discussion of any new technology that affects hydrocarbon recovery systems;

(o) A list of any alternate compliance procedures or departures for which you anticipate requesting approval; and

(p) Payment of the service fee listed in §250.125.

§ 250.293 What operations require approval of the DWOP?

You may not begin production until BSEE approves your DWOP.

§ 250.294 May I combine the Conceptual Plan and the DWOP?

If your development project meets the following criteria, you may submit a combined Conceptual Plan/DWOP on or before the deadline for submitting the Conceptual Plan.

(a) The project is located in water depths of less than 400 meters (1,312 feet); and

(b) The project is similar to projects involving non-conventional production or completion technology for which you have obtained approval previously.

§ 250.295 When must I revise my DWOP?

You must revise either the Conceptual Plan or your DWOP to reflect changes in your development project that materially alter the facilities, equipment, and systems described in your plan. You must submit the revision within 60 days after any material change to the information required for that part of your plan.

Subpart C—Pollution Prevention and Control

§ 250.300 Pollution prevention.

(a) During the exploration, development, production, and transportation of oil and gas or sulphur, the lessee shall take measures to prevent unauthorized discharge of pollutants into the offshore waters. The lessee shall not create conditions that will pose unreasonable risk to public health, life, property, aquatic life, wildlife, recreation, navigation, commercial fishing, or other uses of the ocean.

(1) When pollution occurs as a result of operations conducted by or on behalf of the lessee and the pollution damages or threatens to damage life (including fish and other aquatic life), property, any mineral deposits (in areas leased or not leased), or the marine, coastal, or human environment, the control and removal of the pollution to the satisfaction of the District Manager shall be at the expense of the lessee. Immediate corrective action shall be taken in all cases where pollution has occurred. Corrective action shall be subject to modification when directed by the District Manager.

(2) If the lessee fails to control and remove the pollution, the Director, in cooperation with other appropriate Agencies of Federal, State, and local governments, or in cooperation with the lessee, or both, shall have the right to control and remove the pollution at the lessee's expense. Such action shall

§ 250.301

not relieve the lessee of any responsibility provided for by law.

(b)(1) The District Manager may restrict the rate of drilling fluid discharges or prescribe alternative discharge methods. The District Manager may also restrict the use of components which could cause unreasonable degradation to the marine environment. No petroleum-based substances, including diesel fuel, may be added to the drilling mud system without prior approval of the District Manager.

(2) Approval of the method of disposal of drill cuttings, sand, and other well solids shall be obtained from the District Manager.

(3) All hydrocarbon-handling equipment for testing and production such as separators, tanks, and treaters shall be designed, installed, and operated to prevent pollution. Maintenance or repairs which are necessary to prevent pollution of offshore waters shall be undertaken immediately.

(4) Curbs, gutters, drip pans, and drains shall be installed in deck areas in a manner necessary to collect all contaminants not authorized for discharge. Oil drainage shall be piped to a properly designed, operated, and maintained sump system which will automatically maintain the oil at a level sufficient to prevent discharge of oil into offshore waters. All gravity drains shall be equipped with a water trap or other means to prevent gas in the sump system from escaping through the drains. Sump piles shall not be used as processing devices to treat or skim liquids but may be used to collect treated-produced water, treated-produced sand, or liquids from drip pans and deck drains and as a final trap for hydrocarbon liquids in the event of equipment upsets. Improperly designed, operated, or maintained sump piles which do not prevent the discharge of oil into offshore waters shall be replaced or repaired.

(5) On artificial islands, all vessels containing hydrocarbons shall be placed inside an impervious berm or otherwise protected to contain spills. Drainage shall be directed away from the drilling rig to a sump. Drains and sumps shall be constructed to prevent seepage.

30 CFR Ch. II (7–1–14 Edition)

(6) Disposal of equipment, cables, chains, containers, or other materials into offshore waters is prohibited.

(c) Materials, equipment, tools, containers, and other items used in the Outer Continental Shelf (OCS) which are of such shape or configuration that they are likely to snag or damage fishing devices shall be handled and marked as follows:

(1) All loose material, small tools, and other small objects shall be kept in a suitable storage area or a marked container when not in use and in a marked container before transport over offshore waters;

(2) All cable, chain, or wire segments shall be recovered after use and securely stored until suitable disposal is accomplished;

(3) Skid-mounted equipment, portable containers, spools or reels, and drums shall be marked with the owner's name prior to use or transport over offshore waters; and

(4) All markings must clearly identify the owner and must be durable enough to resist the effects of the environmental conditions to which they may be exposed.

(d) Any of the items described in paragraph (c) of this section that are lost overboard shall be recorded on the facility's daily operations report, as appropriate, and reported to the District Manager.

§ 250.301 Inspection of facilities.

Drilling and production facilities shall be inspected daily or at intervals approved or prescribed by the District Manager to determine if pollution is occurring. Necessary maintenance or repairs shall be made immediately. Records of such inspections and repairs shall be maintained at the facility or at a nearby manned facility for 2 years.

Subpart D—Oil and Gas Drilling Operations

GENERAL REQUIREMENTS

§ 250.400 Who is subject to the requirements of this subpart?

The requirements of this subpart apply to lessees, operating rights owners, operators, and their contractors and subcontractors.